

Desksurfer

Date: 1st July 2020

<u>Model</u>	<u>Reach Height</u>	<u>Min. Plat</u>	<u>Max Plat Height</u>	<u>Mast</u>	<u>No. of Outrigger</u>	<u>Adj. Legs</u>
35UM	3.5m	0.973m	1.519m	Upright mast	2	0
35FM	3.5m	0.973m	1.519m	Fold down	2	0
35RM	3.5m	0.973m	1.519m	Removable mast	2	0
42UM	4.2m	0.875m	2.240m	Upright mast	2	0
42FM	4.3m	0.955m	2.320m	Fold down	2	0
42RM	4.3m	0.955m	2.320m	Removable mast	2	0
49FM	4.9m	1.228m	2.871m	Fold down	4	0
55FM	5.5m	1.589m	3.500m	Fold down	4	8
60FM	6.0m	1.862m	4.046m	Fold down	4	8

<u>Options</u>	<u>Description</u>
Option 1	Transport Dolly
Option 2	Seat/tool tray
Option 3	Insulating platform mat
Option 4	PVC insulation on top handrail horizontal tubes
Option 5	Adjustable legs for Model 35, 42 & 49: - Includes 4 off AL370 legs & 4 off C125N locking castors in lieu of the normal C125E Expanding spigot castors
Option 6	2 off extra outriggers for front of base unit, c/w extra height front posts (standard with models 49, 55 and 60)
Option 7	Desksurfer base tool tray c/w rubber mat (fitted during manufacture)
Option 8	R1884TFH/S/I Special 400mm length top folding handrail c/w insulation on top horizontal tubes (spigot/couple-on)
Option 9	R1884TFHS/S Special 400mm Length top folding handrail (spigot/couple-on)
Option 10	Desksurfer (retro-fit) base tool tray c/w rubber mat
Option 11	Low level base
Option 12	Telescopic base (from 1120mm to 920mm)
Option 13	PVC cover for Desksurfer model 35/42
Option 14	Seat/hop up platform with toe board location, couple on guardrail extension, PVC insulation and 3-sided toe board for use with hop up (option 6 also required)

